

DYDEN CORPORATION

ELECTRIC WIRES
& CABLES PRODUCTS

DATE Feb, 1, 2016

SPEC. No.FSC16-045

SPECIFICATION

FOR

CROSS-LINKED POLYETHYLENE (XLPE) INSULATED
AND PVC JACKETED CABLE WITH SHIELD

(RMCV-SB-Kr (2464))

RoHS correspondence



signed by S. Maeda
S. MAEDA

Manager
Engineering section
Engineering dept
Factory Automation & Robot Cable Division

1. SCOPE

This specification covers the construction, characteristics of the Cross-Linked Polyethylene(XLPE) insulated and PVC jacketed cable with shield .

2. SYMBOL, SIZE

The symbol and size of the cable shall be

“ RMCV-SB-Kr(2464) AWG25/18P ”
(0.2mm²/18P)

3. UL STANDARD

RECONGNIZED by UNDERWRITERS LABORATORIES Inc.

STYLE No.	2464 (UL 758 : AWM)
Rating TEMP.	80°C
VOLT.	300V
USE	Internal wiring or external interconnection of electronic equipment

4. FLAME TESTING

The cable shall pass the vertical wire flame test (VW-1) described in UL1581, Paragraph 1080.

5. CONSTRUCTION

The construction of the cable shall conform to Table 1.

6. CHARACTERISTICS

The characteristics of the cable shall be shown in Table 2.

7. MARKING

The following information shall be indicated with a suitable method to the cable.

“ —DYDEN E91337  AWM 2464 80C 300V VW-1 -LF- RMCV-SB-Kr AWG25/18P — ”

* * * * *

Table 1 Construction


I T E M		V A L U E
Symbol		RMCV-SB-Kr (2464)
Size	AWG (mm ²)	25 (0.2)
Conductor	Material	Annealed Copper
	Construction (No./mm)	40/0.08
	Dia. (approx. mm)	0.58
Insulation	Material	XLPE
	Thickness (approx. mm)	0.20
	Dia. (approx. mm)	0.98
Twisting	Dia. (approx. mm)	2.0
Stranding	Center layer	6 P
	First layer	12 P
Tape	—	Binder tape
Shield (Braid)	Material	Tinned Annealed Copper
	Thickness (approx. mm)	0.35
Jacket	Material (color)	Flame retardant • Oil resistant PVC (Black)
	Thickness (approx. mm)	1.2
Overall diameter (approx. mm)		12.1
Approx. mass (kg/km)		190

Table 2 Characteristics (at 20°C)

I T E M	S T A N D A R D V A L U E
Max. DC resistance of conductor (Ω /km)	101.9
Min. insulation resistance (M Ω -km)	100
Dielectric strength (V/min)	AC 2000

Fig 1

Cross-Section of Cable



PairNo.	Colors	PairNo.	Colors
1	Blue×White	10	Purple×Brown
2	Yellow×White	11	Blue×Black
3	Green×White	12	Yellow×Black
4	Red×White	13	Green×Black
5	Purple×White	14	Red×Black
6	Blue×Brown	15	Purple×Black
7	Yellow×Brown	16	Blue×Gray
8	Green×Brown	17	Yellow×Gray
9	Red×Brown	18	Green×Gray

NOT TO SCALE